# Jack-26 (2,600 lbs. Capacity)

### **Electric Pallet Jack**

MOBILE WEIGHING SCALE

The iJack-26 is an electric pallet jack with a built-in scale designed to weigh and lift loads up to 2,600 lbs. Easy to operate and perfect for navigating tight spaces within trailers and warehouse floors, iJack is powered by a lithium-ion battery and comes standard with wireless connection and NTEP (legal for trade) technology. Ideal for retail and commercial environments, iJack is an efficient, high ROI option for replacing your hand pallet jack or floor scale.

### A Compact, Powerful **Electric Pallet Jack**

- Built-in scale and WiFi-enabled onboard indicator are standard
- Powered by a rechargeable lithium-ion battery
- Ergonomic handle with reversing switch, horn, and intuitive dual thumb controls for safe and accurate operation

2,600 lb.

- Compact body easily navigates tight corners
- NTEP (Legal for Trade) certified





Effortlessly lift and drive

with handle controls



## Jack-26

#### DRIVE AND TRAVEL CONTROLS

- 48-Volt Curtis Travel Control with permanent magnet drive motor
- Variable speed from 0 MPH to 3.4 MPH empty
- Variable speed from 0 MPH to 3.1 MPH loaded

#### STANDARD SPECIFICATIONS

#### **WEIGHT**

• 288 lbs. with Battery

#### **TIRES**

- Drive (1) 8.3" X 2.8" Polyurethane
- Load (2) 2.4" X 3.1" Polyurethane

#### **FORKS**

- 27" OAW X 46" OAL Standard
- Maximum Elevation of 7.5"

#### **CONTROL HEAD**

- Travel, lift & lower functions, and creep speed controls
- · Easy Operation for Either Hand
- Belly Button Reversing Switch, Dural Butterfly Travel Controls, Wake-Up Buttons, and Key Switch
- Low Mounted Tiller Arm for Comfort and Minimum Steering Effort

#### **HYDRAULICS**

DC Pump and Chrome Plated Cylinder

#### **ELECTRICAL**

- Water Resistant Connectors & Wired Harness Supply Power Reliably to Components
- · Emergency Power Disconnect
- Covered On-Board Dock for Easy Exchange


#### **BRAKES**

• Electromagnetic Brakes


#### **SERVICEABILITY**

- Removable Covers & Modular Design of Components
- · Two Piece Drive Wheel
- Easy Exchange HD Battery Delivers up to 3.0 Hours of Operation & Charged within 1.5 Hours
- Temperature range 32°-104°F

#### **DIMENSIONS**



Fork length	45.25"
Fork width	5.9"
Width over fork	27"
Lowered fork height	3.54"
Ground clearance	1.1"
Lifting height	4.5"
Total truck length	60.5"
Truck width	27"
Truck height	46"





 RAVAS WeightsApp for data capture on tablets and smart phones







