

RAVAS-TOUCH GMP

Hygienic stainless steel hand pallet truck



BENEFITS

- Minimal maintenance, easy cleaning and high resistance to corrosion
- Manufactured 100% in stainless steel 304L (1.4307) or 316L (1.4404), including all hydraulic parts
- Open under-fork construction, closed fork-shoe, for maximum hygiene
- Hydraulic equipment contains food grade oil
- Continuous weld: welds are polished
- Electro polishing, for very smooth surfaces

Hygienic

For industrial use



RAVAS

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare via touch screen
- Entry of alphanumeric codes
- Totalling with sequence number
- Piece counting by sampling or entry of piece weights
- Error messages in display
- Internal clock
- USB port for data capture


STANDARD SPECIFICATIONS

- Weighing capacity 5,000 lb
- Graduation multirange:
0 - 400 lb: graduation 0.2 lb
400 - 1,000 lb: graduation 0.5 lb
1,000 - 5,000 lb: graduation 1.0 lb
- Max. tolerance 0.08% of the load lifted
- Display 18 cm / 7.1 inch, high resolution touch screen
- Protection class load cells IP67, indicator IP65
- Battery 12V, by 4 exchangeable battery modules 6V - 4,8Ah
- Battery life 12 hours, charging time 6 hours
- Charger 110V NiMH charger included
- Steering wheels nylon
- Loading wheels nylon, single
- Pump ergonomic lift
- Own weight 375 lb

HYGIENIC CONSTRUCTION

- All bearings are waterproof and self-lubricated
- All moveable parts have polymer bearings, free of lubrication
- Pump function with plastic coated stainless steel cable (no chain)
- Internal dashboard with on/off switch, fuse and USB port
- Completely silicon free

DIMENSION



| | | |
|---|-----------------------|-------|
| A | Fork length | 48" |
| B | Fork width | 7.1" |
| C | Minimum fork height | 3.25" |
| | Space underneath fork | 0.7" |
| D | Maximum fork height | 7.9" |
| | Lifting height | 4.8" |
| E | Width over forks | 27.2" |
| F | Height | 48" |



Management System
ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
www.tuv.com
ID 0000037200

OPTIONS*

- Client specific software
- 4 extra exchangeable batteries
- (internal) USB output for transfer stored weighing data
- External printer via wireless connection to the indicator
- Wireless data transfer to devices that have WiFi or Bluetooth® technology
- Legal for trade version, NTEP
- Rotating indicator
- 0.2 lb graduation, maximum 2,000 lb capacity

RAVAS USA

1500 Enterprise Parkway, Twinsburg, Ohio 44087
T: 330.425.3092 E: salesoffice-usa@ravas.com
WWW.RAVAS.COM

